

# POWER MONITOR

## Model M20

Affordable protection for any FTI pump including UC, DB and SP Series mag drives



### How it works

The M20 utilizes a unique algorithm to measure normal work load and then calculates and sets a shutdown sequence when an increase or decrease in shaft power is detected outside the determined parameters. Pump shut-down takes place before dry-running damage can occur.

### Benefits

- More accurate than amp monitors and motor input power monitors.
- Pump curves express load data in shaft power, not motor input power.
- The significant losses of the motor are removed to improve accuracy and reliability.
- Protection parameters are set against the actual working load.
- The power displayed by the meter is the actual power being used by the pump.

### Features:

- Provides accurate shaft power measurement
- Instantaneously shuts down pump when a change in shaft power is sensed
- Easy to install
- Autoset makes set up quick and easy
- Monitors supply power from line voltage
- Electronically locks parameters
- Digital readout of HP, % HP, kW, % kW, volts and amps
- Programmable relay configurations
- Four levels of protection (pre-alarm minimum & maximum power; alarm minimum & maximum power)
- Just three models cover all motor voltages up to 690 VAC
- Operates at 50 or 60 Hz
- Programmable analog signal proportionate to the motor's shaft power
- UL, cUL and CE approved

### Uses:

- Dry running – Protects pumps with PTFE, silicon carbide or ceramic bushings if no liquid is present.
- Dead heading – Prevents operating the pump with a closed discharge valve or clogged filter.
- Excess power – Prevents failures due to foreign objects being sucked into the pump, changes in system piping, or changes in fluid characteristics such as viscosity or specific gravity.
- SP Series – Delay feature ensures pump is primed and operating.



FINISH THOMPSON INC.